



Your Exhibit Flooring Specialists

Carpet Installation Sheet

Clean/Smooth Surface:

Position and roll out the carpet on a flat surface pulling it firmly to ensure it lies flat to the ground. In most cases the carpet will roll out and be ready for use without further handling. If necessary, you can use Signature's optional grip tape. Grip tape directions are described below.

Plastic/Wood Surface:

For plastic or wood surfaces (tent floor), use heavy duty staples around the edging of the carpet. The staples should be applied 8-10 inches apart on both sides of the carpet. (Note: In high traffic areas both staples and 5" Carpet Grip Tape can be used for a better hold).

Asphalt or Concrete Surfaces:

For asphalt or concrete surfaces, roll out the carpet and pull tight to ensure there is no bunching of the carpet. Optional 3" duct tape may be used to affix the carpet to either surface. The 3" duct tape should be applied to all sides of the carpet along the perimeter, with half of the tape being applied to the carpet, while the other half is applied to the sub-surface. Numerous layers of tape may be needed to hold the carpet in place and to ensure a professional appearance.

Using Grip Tape

Grip tape is the most commonly utilized product for affixing carpet to any surface. Grip tape is easy to use and can often be re-used as many as four times. It leaves no residue and can be installed by just about anyone. To use grip tape, start out by removing the clear protective film from the tape, and affixing the sticky tape to the underside of the carpet. Once the tape is secured to the carpet, remove the yellow backing from the tape and place the carpet onto the floor. For the best results, apply the tape to the underside of all edges of the carpet and press down firmly to the subsurface.



50 East 42nd Street - 14th Floor New York, NY 10017
212-953-1116 -- 212-953-1117 Fax -- 800-569-2751 Toll Free