



PRODUCT SPECIFICATIONS

Description:	Heavy duty, roll-out mats and interlocking rubber tiles for cushioned support.
Standard Colors:	Solid Black, Blue Flec, Gray Flec, Yellow Flec, Green Flec, Red Flec, Blue/Gray Flec. Custom colors available.
Material:	Recycled rubber and polymer binding agents.
Size:	
Interlocking Tiles:	28.5" x 28.5"
Thickness:	0.375"
Weight:	11.28 lbs.
Chemical Behavior:	Resistant to water, numerous diluted acids and alkaline solutions. Chemically neutral. UV Resistant.
Density:	60 lbs./ft ³ ASTM D 3676
Elongation:	< 145%
Shearing Strength:	< 0.60 (N/mm ²)
Tensile Strength:	< 1.80 (N/mm ²)
Temperature Stability:	-30°C up + 80°C in resting conditions
Flammability:	Passes Federal Flammability Standard Doc FF 1-70 CPSC.
Friction Coefficient:	0.96 dry

Compression &

Recovery: After 48 hours 99.4%
ASTM D 575 After 72 hours 99.7%
After 96 hours 99.7%

ACCESSORIES

Polyurethane

Adhesive:

1. One-component polyurethane-based trowel-grade, structural adhesive.
2. Suitable for indoor and outdoor applications.
3. Covers 60 sq/ft per gallon.
4. Provides excellent initial grab and outstanding bond strength.
5. No Water – Freeze/thaw stable.
6. Meets flame spread requirements: NFPA – Class A, and UBC – Class I.
7. VOC compliant, extremely low odor.
8. Can be used on concrete, plywood, particle/chip board, cement and gypsum underlayment, radiant heat flooring, and asphalt.
9. Application temperature: above 40°F

Double-Sided

Carpet Tape:

1. 5” W x 60’ L

Edging:

1. 12 ft long.
2. Usable with 0.375” mat thickness only.
3. Use carpet tape to secure in position.

Warranty:

2-year warranty against manufacturer’s defects.

