



### PRODUCT SPECIFICATIONS - UltraDeck

**Module Size:**

**Width:** 24" / 60.96 cm / 609.6 mm  
**Length:** 12" / 30.48 cm / 304.8 mm  
**Thickness:** 1.125" Tall / 2.858 cm / 28.58 mm

**Module Weight:** 2.88 lbs. / 46.08 oz. / 1.306 kg. / 1306 grams  
**Per Square Foot:** 1.44 lbs. / 23.04 oz. / 0.653 kg. / 653 grams  
**Per Square Meter:** 15.50 lbs. / 7.03 kg.

**Material:** High-impact polypropylene co-polymer. UV Inhibitors added.

**Fire Rating:** UL 94HB (Underwriters Laboratory Yellow Card Number)  
This test signifies that this product does not flare up when exposed to an open flame and has a slow burn rate of 2" per minute for a 2" wide, 0.5 millimeter thickness test sample.  
ASTM 2859 (Flammability of Finished Texture Floor Covering Materials)  
– passed test  
\* Testing reports available for fire ratings

**Hot Wire Ignition Rating:** 3

**Melting Point:** 324 Fahrenheit / 162 Celcius  
**Operating Range:** -10° F → 150°F / -23.33° C → 65.56° C

**Support Structure:** Flooring module incorporates multi-directional structural support ribbing, allowing for distribution of weight and loads.

**Weight Loading:** 20,000 lbs sq/ft static load, solid sub-surface. Varies depending on sub-surface.

**Ground Surfaces:** UltraDeck is designed to be used with little ground preparation over grass, gravel, sand, soil, concrete, asphalt, ice, snow, mud, synthetic turf, rubberized tracks, and other standard surfaces.



<b>Shipping:</b>	40" x 48" Pallet:	up to 816 sq/ft
	463L Pallet (83"L x 103"W x 96"H Max):	3,312 sq/ft
	20' Ocean Container:	8,160 sq/ft
	40' Ocean Container:	16,320 sq/ft
	Note: High cube container loads can be loaded with additional product.	
	48' Truck:	19,684 sq/ft
	53' Truck:	21,216 sq/ft

**Functional Features:**

- a) Individual modules interconnect to form larger flooring sections.
- b) Connection system allows for installation and disassembly *without* the need for connection or separation tools.
- c) Modules feature integrated, multi-directional cable channels on the underside of each tread, for running power and communication wiring or rope lighting.
- d) Modules are designed to allow 90-degree rotation and still connect. Module can be connected in both directions and at any module connection point, allowing greater flexibility in floor design.
- e) Modules do not have any submerged channels into which debris or dirt can enter from the top surface, and are easy to clean and maintain.

**Warranty:** 3 Year warranty against manufacturer's defects.



Your Exhibit Flooring Specialists